JJMICROELECTRONICS

650V 15A Trench and Field Stop IGBT

JJT15N65SS

Key performance:

- V_{CE}=650V
- I_C=15A@T_C=100℃
- $V_{CE(sat)}$=1.6 V

TO-220F



Features:

- High ruggedness performance.
- 10μs short circuit capability.
- Positive $V_{CE\ (sat)}$ temperature coefficient.
- High efficiency for motor control.
- Excellent current sharing in parallel operation.
- RoHS compliant.



Applications:

- Home appliances
- Motor drives
- General inverter

Package parameters

Type	Marking	Package	Packaging method
JJT15N65SS	T1565SS	TO-220F	Tube

All product information is copyrighted and subject to legal disclaimers.

Maximum ratings

Symbol	Parameter	Values	Unit
V_{CES}	Collector-emitter voltage	650	V
V_{GES}	Gate-emitter voltage	±20	V
I_C	Continuous collector current (T_C=25℃)	30	A
	Continuous collector current (T_C=100℃)	15	A
I_{CM}	Pulsed collector current, t_p limited by T_{vjmax}	60	A
I_F	Diode continuous forward current (T_C=100℃)	15	A
I_{FM}	Diode maximum current, t_p limited by T_{vjmax}	60	A
t_{sc}	Short circuit withstand time	10	μs
P_{tot}	Power dissipation (T_C=25℃)	71	W
	Power dissipation (T_C=100℃)	36	W
T_{vj}	Operating junction temperature range	-40 to +175	℃
T_{stg}	Storage temperature range	-55 to +150	℃

Thermal characteristics

Symbol	Parameter	Values		Unit
		Typ.	Max.	
$R_{th(j-c)}$	Thermal resistance, junction to case for IGBT	-	2.1	K/ W
$R_{th(j-c)}$	Thermal resistance, junction to case for Diode	-	3.2	K/ W
$R_{th(j-a)}$	Thermal resistance, junction to ambient	-	70	K/ W

All product information is copyrighted and subject to legal disclaimers.

Electrical characteristics of IGBT (T_{vj}=25℃ unless otherwise specified)

Static characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
BV_{CES}	Collector-emitter breakdown voltage	V_{GE}=0V, I_C=250μA	650	-	-	V
I_{CES}	Collector-emitter leakage current	V_{CE}=650V, V_{GE}=0V	-	-	50	μA
I_{GES}	Gate leakage current, forward	V_{GE}=20V, V_{CE}=0V	-	-	100	nA
	Gate leakage current, reverse	V_{GE}=-20V, V_{CE}=0V	-	-	-100	nA
$V_{GE(th)}$	Gate-emitter threshold voltage	V_{GE}=V_{CE}, I_C=1mA	5.1	5.6	6.1	V
$V_{CE(sat)}$	Collector-emitter saturation voltage	V_{GE}=15V, I_C=15A	-	1.6	-	V
		V_{GE}=15V, I_C=15A,T_{vj}=175℃	-	2.1	-	V

Dynamic characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
C_{ies}	Input capacitance	V_{CE}=30V V_{GE}=0V f=1MHz	-	1055	-	pF
C_{oes}	Output capacitance		-	57	-	pF
C_{res}	Reverse transfer capacitance		-	15	-	pF
Q_g	Total gate charge	V_{CC}=520V V_{GE}=15V I_C=15A	-	55	-	nC

All product information is copyrighted and subject to legal disclaimers.

Switching characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
$t_{d(on)}$	Turn-on delay time	V_{CC}=400V V_{GE}=0/15V I_C=15A R_G=10Ω Inductive load	-	15	-	ns
t_r	Rise time		-	17	-	ns
$t_{d(off)}$	Turn-off delay time		-	110	-	ns
t_f	Fall time		-	73	-	ns
E_{on}	Turn-on energy		-	0.38	-	mJ
E_{off}	Turn-off energy		-	0.37	-	mJ
E_{ts}	Total switching energy		-	0.75	-	mJ
$t_{d(on)}$	Turn-on delay time	V_{CC}=400V V_{GE}=0/15V I_C=15A R_G=10Ω Inductive load T_{vj}=175℃	-	14	-	ns
t_r	Rise time		-	18	-	ns
$t_{d(off)}$	Turn-off delay time		-	146	-	ns
t_f	Fall time		-	158	-	ns
E_{on}	Turn-on energy		-	0.44	-	mJ
E_{off}	Turn-off energy		-	0.64	-	mJ
E_{ts}	Total switching energy		-	1.08	-	mJ

All product information is copyrighted and subject to legal disclaimers.

Electrical characteristics of Diode (T_{vj}=25℃ unless otherwise specified)

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
V_F	Diode forward voltage	I_F=15A	-	1.4	-	V
		I_F=15A,T_{vj}=175℃	-	1.1	-	V
t_{rr}	Diode reverse recovery time	V_R=400V I_F=15A di_F/dt=-600A/μs	-	55	-	ns
I_{rrm}	Diode peak reverse recovery current		-	9.5	-	A
Q_{rr}	Diode reverse recovery charge		-	220	-	nC
t_{rr}	Diode reverse recovery time	V_R=400V I_F=15A di_F/dt=-600A/μs T_{vj}=175℃	-	77	-	ns
I_{rrm}	Diode peak reverse recovery current		-	15	-	A
Q_{rr}	Diode reverse recovery charge		-	481	-	nC

All product information is copyrighted and subject to legal disclaimers.

Typical performance characteristics



Fig 1. Typical output characteristic (T_{vj}=25℃)



Fig 2. Typical output characteristic(T_{vj}=175℃)



Fig 3. Power dissipation as a function of T_C



Fig 4. Typical I_F as a function of V_F



Fig 5. Typical $V_{GE(th)}$ as a function of T_{vj} (I_C=1mA)



Fig 6. Typical V_F as a function of T_{vj}

All product information is copyrighted and subject to legal disclaimers.

Typical performance characteristics



Fig 7. Typical V_{CEsat} as a function of T_{vj}



Fig 8. Typical Gate charge



Fig 9. Typical capacitance as a function of V_{CE} (f=1Mhz, V_{GE}=0V)



Fig 10. Typical switching times as a function of I_C



Fig 11. Typical switching energy losses as a function of I_C



Fig 12. Typical switching times as a function of R_G

All product information is copyrighted and subject to legal disclaimers.

Typical performance characteristics



Fig 13. Typical switching energy losses as a function of R_G



Fig 14. Transient thermal impedance, IGBT

All product information is copyrighted and subject to legal disclaimers.

Package dimension

TO-220F



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.50	-	4.90	0.177	-	0.193
B	0.74	0.80	0.83	0.029	0.031	0.033
C	0.47	-	0.66	0.019	-	0.026
C2	2.45	-	2.75	0.096	-	0.108
C3	2.60	-	3.00	0.102	-	0.118
D	8.80	-	9.30	0.346	-	0.366
E	9.80	-	10.40	0.386	-	0.410
F	6.40	-	6.80	0.252	-	0.268
G	2.40	-	2.70	0.094	-	0.106
H	28.0	-	29.80	1.102	-	1.173
L1	-	3.63	-	-	0.143	-
L2	1.14	-	1.70	0.045	-	0.067
L3	-	3.30	-	-	0.130	-
V1	-	45°	-	-	45°	-

All product information is copyrighted and subject to legal disclaimers.

Revision history

Date	Revision	Changes
2023-11-27	Rev 1.1	Update
2024-03-18	Rev 1.2	Update
2025-04-08	Rev 1.3	Character Update
2026-06-24	Rev 1.4	Update thermal

Disclaimer

PLEASE NOTE - Jiangsu JieJie Microelectronics Co., Ltd ("JJM") reserves the right to amend, correct, modify and enhance the product and/or this document at any time without prior notice. If you intend to purchase this product, please obtain the latest information available before placing your order. The sale of JJM products is governed by JJM's prevailing terms and conditions at the time of purchase and purchasers are solely responsible for the selection and use of the products with no liability on JJM's part to supply application assistance or customization. Purchase of JJM products does not grant the purchaser license, express or implied, to JJM's intellectual property. Any warranties provided with JJM products are null and void upon resale unless accompanied by the information set forth herein in its entirety. The JJM name and logo are registered trademarks of Jiangsu JieJie Microelectronics Co., Ltd. This document supersedes all previous versions. ©2026 JJM - All rights reserved