Description

JMT P-channel Enhancement Mode Power MOSFET

Features

- -20V, -5A
  $R_{DS(ON)}$<26mΩ @ V_{GS}=-4.5V
  $R_{DS(ON)}$<37mΩ @ V_{GS}=-2.5V
- Advanced Trench Technology
- Provide Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead free product is acquired

Application

- Load Switch
- PWM Application
- Power management

RoHS



SOT-23-3L top view



Marking and pin Assignment



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	OUTLINE	Device Package	Reel Size	Reel (PCS)	Per Carton (PCS)
2025	JMTJ250P02A	TAPING	SOT-23-3L	7inch	3000	120000

Absolute Maximum Ratings (T_A=25℃ unless otherwise specified)

Symbol	Parameter		Max.	Units
V_{DSS}	Drain-Source Voltage		-20	V
V_{GSS}	Gate-Source Voltage		±12	V
I_D	Continuous Drain Current	T_A= 25℃	-5	A
		T_A= 100℃	-3.25	A
I_{DM}	Pulsed Drain Current note1		-20	A
P_D	Power Dissipation	T_A= 25℃	1.1	W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient		114	℃/W
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to +150	℃

Electrical Characteristics (T_J=25℃ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D= -250μA	-20	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}= -20V, V_{GS}=0V,	-	-	-1	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS}=0V, V_{GS}= ±12V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D= -250μA	-0.4	-0.7	-1.0	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note2	V_{GS}= -4.5V, I_D= -5A	-	20	26	mΩ
		V_{GS}= -2.5V, I_D= -4A	-	27	37	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}= -10V, V_{GS}=0V, f=1.0MHz	-	1200	-	pF
C_{oss}	Output Capacitance		-	191	-	pF
C_{rss}	Reverse Transfer Capacitance		-	168	-	pF
Q_g	Total Gate Charge	V_{DS}= -10V, I_D= -5A, V_{GS}= -4.5V	-	33.7	-	nC
Q_{gs}	Gate-Source Charge		-	3.5	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	10.5	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DD} = -10V, I_D= -5A, V_{GS}= -4.5V,R_{GEN}=10Ω	-	11	-	ns
t_r	Turn-on Rise Time		-	35	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	30	-	ns
t_f	Turn-off Fall Time		-	10	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	-5	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	-20	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS}=0V, I_S= -5A	-	-	-1.2	V

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. Pulse Test: Pulse Width≤300μs, Duty Cycle≤2%

Typical Performance Characteristics

Figure1: Output Characteristics



Figure 2: Typical Transfer Characteristics



Figure 3: On-resistance vs. Drain Current



Figure 4: Body Diode Characteristics



Figure 5: Gate Charge Characteristics



Figure 6: Capacitance Characteristics



Figure 7: Normalized Breakdown Voltage vs. Junction Temperature



Figure 8: Normalized on Resistance vs. Junction Temperature



Figure 9: Maximum Safe Operating Area



Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature



Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



Test Circuit

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Package Mechanical Data- SOT-23-3L



COMMON DIMENSIONS
(UNITS OF MEASURE=mm)

SYMBOL	MIN	NOM	MAX
A	——	——	1.30
A1	0.00	0.05	0.10
A2	1.00	1.10	1.20
b	0.30	0.40	0.50
c	0.119	0.127	0.135
e1	1.80	1.90	2.00
D	2.80	2.90	3.00
E	1.50	1.60	1.70
E1	2.60	2.80	3.00
L	0.30	0.45	0.60
θ	0°	4°	8°
e	0.95BSC		

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.
Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.
Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.
is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.
Copyright ©2022 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.