



## Description

### JMT N-channel Enhancement Mode Power MOSFET

#### Features

- 30V, 13A
- $R_{DS(ON)} < 12m\Omega$  @  $V_{GS} = 10V$
- $R_{DS(ON)} < 18m\Omega$  @  $V_{GS} = 4.5V$
- Advanced Trench Technology
- Provide Excellent  $R_{DS(ON)}$  and Low Gate Charge
- Lead free product is acquired


#### Application

- Load Switch
- PWM Application
- Power management




100% UIS TESTED!


100%  $\Delta V_{ds}$  TESTED!



SOP-8 TOP View



Marking and pin Assignment



Schematic Diagram

## Package Marking and Ordering Information

Device Marking	Device	OUTLINE	Device Package	Reel Size	Reel (PCS)	Per Carton (PCS)
4406A	JMTP4406A	TAPING	SOP-8	13inch	4000	48000

## Absolute Maximum Ratings ( $T_A=25^\circ C$ unless otherwise specified)

Symbol	Parameter		Max.	Units
$V_{DSS}$	Drain-Source Voltage		30	V
$V_{GSS}$	Gate-Source Voltage		$\pm 20$	V
$I_D$	Continuous Drain Current	$T_A = 25^\circ C$	13	A
		$T_A = 100^\circ C$	8.5	A
$I_{DM}$	Pulsed Drain Current <sup>note1</sup>		52	A
$E_{AS}$	Single Pulsed Avalanche Energy <sup>note2</sup>		33	mJ
$P_D$	Power Dissipation	$T_A = 25^\circ C$	3.5	W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient		35.7	$^\circ C/W$
$T_J, T_{STG}$	Operating and Storage Temperature Range		-55 to +150	$^\circ C$

**Electrical Characteristics** ( $T_J=25^\circ\text{C}$  unless otherwise specified)


Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
<b>Off Characteristic</b>						
$V_{(\text{BR})\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{GS}=0\text{V}$ , $I_D=250\mu\text{A}$	30	-	-	V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=30\text{V}$ , $V_{GS}=0\text{V}$ ,	-	-	1.0	$\mu\text{A}$
$I_{GSS}$	Gate to Body Leakage Current	$V_{DS}=0\text{V}$ , $V_{GS}=\pm 20\text{V}$	-	-	$\pm 100$	nA
<b>On Characteristics</b>						
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$ , $I_D=250\mu\text{A}$	1.0	1.5	2.5	V
$R_{DS(\text{on})}$ note3	Static Drain-Source on-Resistance	$V_{GS}=10\text{V}$ , $I_D=13\text{A}$	-	8.8	12	$\text{m}\Omega$
		$V_{GS}=4.5\text{V}$ , $I_D=10\text{A}$	-	13	18	
<b>Dynamic Characteristics</b>						
$C_{iss}$	Input Capacitance	$V_{DS}=15\text{V}$ , $V_{GS}=0\text{V}$ , $f=1.0\text{MHz}$	-	1011	-	pF
$C_{oss}$	Output Capacitance		-	142	-	pF
$C_{rss}$	Reverse Transfer Capacitance		-	119	-	pF
$Q_g$	Total Gate Charge	$V_{DS}=15\text{V}$ , $I_D=6\text{A}$ , $V_{GS}=10\text{V}$	-	19	-	nC
$Q_{gs}$	Gate-Source Charge		-	6.3	-	nC
$Q_{gd}$	Gate-Drain("Miller") Charge		-	4.5	-	nC
<b>Switching Characteristics</b>						
$t_{d(on)}$	Turn-on Delay Time	$V_{DS}=15\text{V}$ , $I_D=13\text{A}$ , $R_{\text{GEN}}=3\Omega$ , $V_{GS}=10\text{V}$	-	6	-	ns
$t_r$	Turn-on Rise Time		-	5	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	25	-	ns
$t_f$	Turn-off Fall Time		-	7	-	ns
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>						
$I_s$	Maximum Continuous Drain to Source Diode Forward Current	-	-	13	-	A
$I_{SM}$	Maximum Pulsed Drain to Source Diode Forward Current	-	-	52	-	A
$V_{SD}$	Drain to Source Diode Forward Voltage	$V_{GS}=0\text{V}$ , $I_s=13\text{A}$	-	-	1.2	V
$trr$	Body Diode Reverse Recovery Time	$I_F=13\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$	-	7	-	ns
$Qrr$	Body Diode Reverse Recovery Charge		-	6.3	-	nC

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature


2. EAS condition:  $T_J=25^\circ\text{C}$ ,  $V_{GS}=15\text{V}$ ,  $R_G=25\Omega$ ,  $L=0.5\text{mH}$ ,  $I_{AS}=11.5\text{A}$ 3. Pulse Test: Pulse Width $\leq 300\mu\text{s}$ , Duty Cycle $\leq 0.5\%$

## Typical Performance Characteristics


**Figure 1:** Output Characteristics




**Figure 3:** On-resistance vs. Drain Current




**Figure 5: Gate Charge Characteristics**




**Figure 2:** Typical Transfer Characteristics




**Figure 4:** Body Diode Characteristics




**Figure 6:** Capacitance Characteristics




**Figure 7:** Normalized Breakdown Voltage vs. Junction Temperature




**Figure 8:** Normalized on Resistance vs. Junction Temperature




**Figure 9:** Maximum Safe Operating Area



**Figure.11:** Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



**Figure 10:** Maximum Continuous Drain Current vs. Ambient Temperature



## Test Circuit




Figure1:Gate Charge Test Circuit & Waveform



Figure 2: Resistive Switching Test Circuit & Waveforms





Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms



## Package Mechanical Data- SOP-8



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

**J** is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.  
Copyright ©2020 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.