JOCT214Xt-S4 Series

Rev.A.1.0

DESCRIPTION:

The products are transistor opto-couplers in a SSOP4 package. The device is a photoelectric coupler composed of light-emitting diode and phototransistor. The products are widely used in switching power supply, intelligent meter, industrial control, measuring instruments, office equipment such as copiers, household appliances: such as air conditioners, fans, water heaters,etc.



MAIN FEATURES

High isolation 3750 VRMS
Operating temperature range -55°C to 125°C
RoHS & REACH Compliance
HBM: H3A; MM: M4; CDM:C3
CQC approved
VDE approved
UL approved

ABSOLUTE MAXIMUM RATINGS (Temperature=25°C)

Parameter		Symbol	Value	Unit
Input	Forward Current	I_F	±50	mA
	Peak Forward Current	I_{FP}	1①	A
	Power Dissipation	P_D	75	mW
Output	Collector-emitter Voltage	V_{CEO}	80	V
	Emitter-collector Voltage	V_{ECO}	7	V
	Collector Current	I_C	50	mA
	Power Dissipation	P_C	150	mW
Total Power Dissipation		P_{tot}	225	mW
Isolation Voltage		V_{iso}	3750②	Vrms
Operating Temperature		T_{opr}	-55~+125	℃
Junction Temperature		T_j	135	℃
Storage Temperature		T_{stg}	-55~+125	℃
Soldering Temperature		T_{sol}	260	℃

NOTE1: 1 μs pulse **NOTE2**: AC for 1minute, R.H.=40~60%

ELECTRICAL CHARACTERISTICS (Temperature=25°C)

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit
Input	Forward Voltage	V_F	I_F=±10mA	1.1	-	1.7	V
	Terminal Capacitance	C_t	V=0, f=1MHz	-	30	250	pF
Output	Collector-Emitter dark current	I_{CEO}	V_{CE}=20V, I_F=0	-	-	50	nA
	Collector-Emitter breakdown voltage	BV_{CEO}	I_C=0.1mA I_F=0	80	-	-	V
	Emitter-Collector breakdown voltage	BV_{ECO}	I_E=0.1mA I_F=0	7	-	-	V
Transfer Characteristics	Current transfer ratio	CTR①	I_F=±5mA V_{CE}=5V	100	-	400	%
	Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	I_F=±10mA I_C= 1mA	-	0.07	0.2	V
	Isolation resistance	R_{IO}	DC500V 40~60%R.H.	5×10^{10}	10^{11}	-	Ω
	Floating Capacitance	C_{IO}	V=0, f=1MHz	-	0.3	1	pF
	Cut-off Frequency	f_c	V_{CE}=5V, I_C=2mA R_L=100Ω, -3dB	-	80	-	kHz
	Rise Time	t_r	V_{CE}=2V, I_C=2mA R_L=100Ω	-	4	18	μs
	Fall Time	t_f		-	3	18	μs
	Response Time	t_{on}		-	9	25	μs
		t_{off}		-	5	25	μs

NOTE1: Rank Table of Current Transfer Ratio (Temperature=25°C)

CTR Rank	Min. (%)	Max. (%)	Test Condition
P	200	400	I_F=±0.5mA, V_{CE}=5V
	200	400	I_F=±5mA, V_{CE}=5V
Q	100	300	I_F=±0.5mA, V_{CE}=5V
	100	300	I_F=±5mA, V_{CE}=5V

ORDERING INFORMATION



Packing Quantity			
Option	**Quantity**	**Quantity – Inner box**	**Quantity –Outer box**
SSOP4	3000 Units/Reel	2 Reels/Inner box	5 Inner box/Outer box =30k Units

MARKING



Characteristics Curves

FIG.1: Max. Allowable LED Forward Current vs. Ambient Temperature



FIG.2: Collector Power Dissiption vs. Ambient Temperature



FIG.3: Forward Current vs. Forward Voltage



FIG.4: Normalized Collector Dark Current vs. Ambient Temperature



FIG.5: Collector Current vs. Collector-emitter Voltage



FIG.6: Normalized Current Transfer Ratio vs. Forward Current



FIG.7: Normalized Current Transfer Ratio vs. Ambient Temperature



FIG.8: Normalized Collector-emitter Saturation Voltage vs. Ambient Temperature



FIG.9: Response Time vs. Load Resistance



FIG.10: Frequency Response



Test Circuits

FIG.11: Test Circuits of Response Time



FIG.12: Curves of Response Time



Package Dimension (Unit: mm)



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.80	0.173		0.189
B	2.40		2.80	0.094		0.110
C	0.00		0.20	0.000		0.008
D	1.98		2.18	0.078		0.086
E	5.00		5.60	0.197		0.220
F	0.39		0.89	0.015		0.035
G	6.70		7.30	0.264		0.287
H	0.10		0.30	0.004		0.012
I	1.88		2.48	0.074		0.098
J	0.30		0.50	0.012		0.020
K	1.02		1.52	0.040		0.060

RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)



CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option None



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D0		1.50	1.60		0.059	0.063
P0	3.90	4.00	4.10	0.154	0.157	0.161
P1	7.90	8.00	8.10	0.311	0.315	0.319
P2	1.90	2.00	2.10	0.075	0.079	0.083
E	1.65	1.75	1.85	0.065	0.069	0.073
F	5.40	5.50	5.60	0.213	0.217	0.220
T	0.20	0.25	0.30	0.008	0.010	0.012
W	11.90	12.10	12.30	0.469	0.476	0.484

Option R



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D0		1.50	1.60		0.059	0.063
P0	3.90	4.00	4.10	0.154	0.157	0.161
P1	7.90	8.00	8.10	0.311	0.315	0.319
P2	1.90	2.00	2.10	0.075	0.079	0.083
E	1.65	1.75	1.85	0.065	0.069	0.073
F	5.40	5.50	5.60	0.213	0.217	0.220
T	0.20	0.25	0.30	0.008	0.010	0.012
W	11.90	12.10	12.30	0.469	0.476	0.484

REFLOW INFORMATION



Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (Tsmin)	100℃	150℃
Temperature Max. (Tsmax)	150℃	200℃
Time (ts) from (Tsmin to Tsmax)	60-120 seconds	60-120 seconds
Ramp-up Rate (tL to tP)	3℃/second max.	3℃/second max.
Liquidus Temperature (TL)	183℃	217℃
Time (tL) Maintained Above (TL)	60-150 seconds	60-150 seconds
Peak Body Package Temperature	235℃+0℃/-5℃	260℃+0℃/-5℃
Time (tP) within 5℃ of 260℃	10 seconds	10 seconds
Ramp-down Rate (TP to TL)	3-6℃/second	3-6℃/second
Time 25℃ to Peak Temperature	6 minutes max.	8 minutes max.

Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.

2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.

3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.

4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.

5. The component has a shelf life of one year when stored under standard conditions.

6. Recommend storage Temp.: 0~40°C;

Recommend storage humidity: <60%;

MSL level: MSL 1

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2026 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.