JMG50PM12P3S1

Trench FS IGBT

Features

- High Power Density
- High mechanical robustness
- Compact design
- Isolated heatsink using DBC technology
- Very low forward voltage drop
- Fast & soft reverse recovery anti-parallel FWD

Product Summary

Parameter	Value	Unit
V_{CES}	1200	V
I_C(@ T_C= 100℃)	50	A
I_{CRM}(@ t_P= 1ms)	100	A
$V_{CE(sat)}$(Typ)	1.80	V

Applications

- Active Rectifier
- Air Conditioning
- Motor Drives



IGBT, Inverter Absolute Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Collector-emitter voltage	T_{vj} = 25°C	V_{CES}	1200	V
Gate-emitter peak voltage		V_{GES}	±20	V
Continuous collector current	T_c = 100°C	I_C	50	A
Repetitive peak collector current	t_P = 1ms	I_{CRM}	100	A
Total power dissipation	T_C = 25°C, T_{vj} = 175°C	P_{tot}	250	W

Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

IGBT, Inverter Electrical Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	I_C = 50A V_{GE} = 15V	T_{vj} = 25°C	$V_{CE(sat)}$		1.80	2.20	V
		T_{vj} = 125°C			2.10		
		T_{vj} = 150°C			2.20		
Gate threshold voltage	V_{CE}=V_{GE}, I_C=1mA		$V_{GE(th)}$	5.4	6.0	6.6	V
Gate-emitter leakage current	V_{CE} = 0V, V_{GE} = 20V		I_{GES}			400	nA
Collector-emitter cut-off current	V_{CE}=1200V，V_{GE}=0V		I_{CES}			1	mA
Input capacitance	f = 1MHz, T_{vj} = 25°C, V_{CE} = 25 V, V_{GE} = 0 V		C_{ies}		7.76		nF
Reverse transfer capacitance			C_{res}		0.22		nF
Gate charge	V_{GE} = -15V…+15V		Q_G		0.58		μC
Internal gate resistor			R_{Gint}		5.0		Ω,
Turn-on delay time, inductive load	V_{CE} = 600V, I_C = 50A, R_G =15Ω, V_{GE} = ±15V, T_{vj} = 25℃		$t_{d(on)}$		158		ns
Rise time, inductive load			t_r		94		ns
Turn-off delay time, inductive load			$t_{d(off)}$		208		ns
Fall time, inductive load			t_f		142		ns
Turn-on energy loss per pulse			E_{on}		5.60		mJ
Turn-off energy loss per pulse			E_{off}		2.84		mJ
Turn-on delay time, inductive load	V_{CE} = 600V, I_C = 50A, R_G =15Ω, V_{GE} = ±15V, T_{vj} = 125℃		$t_{d(on)}$		152		ns
Rise time, inductive load			t_r		104		ns
Turn-off delay time, inductive load			$t_{d(off)}$		248		ns
Fall time, inductive load			t_f		179		ns
Turn-on energy loss per pulse			E_{on}		8.30		mJ
Turn-off energy loss per pulse			E_{off}		3.70		mJ
SC Data	tp≤10us，V_{GE}≤15V， V_{CC}=900V, V_{CEM}≤1200V T_{vj}=125℃		I_{SC}		300		A
Thermal resistance, junction to case	per IGBT		$R_{th(j-c)}$			0.60	K/W
Temperature under switching conditions			$T_{vj\ op}$	-40		150	℃

Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

FRED, Inverter Absolute Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	T_{vj} = 25°C	V_{RRM}	1200	V
Continuous DC forward current		I_F	50	A
Repetitive peak forward current	t_P = 1ms	I_{FRM}	100	A
I^2t value for fusing	t = 10ms, V_R = 0V, T_{vj} =150°C,	I^2t	220	A^2s

FRED, Inverter Electrical Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage	I_F = 50A, V_{GE} = 0V	T_{vj} = 25°C	V_F		2.10	2.40	V
		T_{vj} = 125°C			1.80		
		T_{vj} = 150°C			1.70		
Peak reverse recovery current	I_F=50A, V_R=600V, V_{GE}=-15V, di/dt=400A/μs	T_{vj} = 25°C	I_{RM}		11.7		A
		T_{vj} = 125°C			18.5		
Recovery charge		T_{vj} = 25°C	Q_{rr}		1.60		μC
		T_{vj} = 125°C			4.74		
Peak reverse recovery energy		T_{vj} = 25°C	E_{rec}		0.45		mJ
		T_{vj} = 125°C			1.30		
Thermal resistance, junction to case	per diode		$R_{th(j-c)}$			1.06	K/W
Temperature under switching conditions			$T_{vj\ op}$	-40		150	℃

Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

Diode, Rectifier Absolute Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	T_{vj} = 25°C	V_{RRM}	1600	V
Bridge output current	T_C = 80℃	I_D	50	A
Repetitive peak forward current	t_P = 10 ms, T_{vj} = 25°C	I_{FSM}	600	A
	t_P = 10 ms, T_{vj} = 150°C		470	
I^2t value for fusing	t_P = 10 ms, T_{vj} = 25°C	I^2t	1800	A^2s
	t_P = 10 ms, T_{vj} = 150°C		1100	

Diode, Rectifier Electrical Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	T_{vj} = 150°C, I_F=50A	V_F		1.0		V
Reverse current	T_{vj} = 25°C, V_R=1600V	I_R			0.1	mA
	T_{vj} = 150°C, V_R=1600V				2	mA
Thermal resistance, junction to case	per diode	$R_{th(j-c)}$			0.65	K/W
Temperature under switching conditions		$T_{vj\ op}$	-40		150	℃

IGBT, Brake-Chopper Absolute Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Collector-emitter voltage	T_{vj} = 25°C	V_{CES}	1200	V
Gate-emitter peak voltage		V_{GES}	±20	V
Continuous collector current	T_C = 100°C	I_C	40	A
Repetitive peak collector current	t_P = 1ms	I_{CRM}	80	A
Total power dissipation	T_C = 25°C, T_{vj} = 175°C	P_{tot}	166	W

Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

IGBT, Brake-Chopper Electrical Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	I_C = 40A, V_{GE} = 15V	T_{vj} = 25°C	$V_{CE(sat)}$		1.80	2.15	V
		T_{vj} = 125°C			2.25		
		T_{vj} = 150°C			2.35		
Gate threshold voltage	V_{CE}=V_{GE}, I_C=0.7mA，		$V_{GE(th)}$	5.4	6.0	6.6	V
Gate-emitter leakage current	V_{CE} = 0V, V_{GE} = 20V		I_{GES}			400	nA
Collector-emitter cut-off current	V_{CE}=1200V， V_{GE}=0V		I_{CES}			1	mA
Input capacitance	f = 1MHz, T_{vj} = 25°C, V_{CE} = 25 V, V_{GE} = 0 V		C_{ies}		5.18		nF
Reverse transfer capacitance			C_{res}		0.15		nF
Gate charge	V_{GE} = -15V…+15V		Q_G		0.39		μC
Internal gate resistor			R_{Gint}		5.0		Ω
Turn-on delay time, inductive load	V_{CC} = 600V, I_C = 40A, R_G = 15Ω, V_{GE} = ±15V, T_{vj} = 25℃		$t_{d(on)}$		104		ns
Rise time, inductive load			t_r		89		ns
Turn-off delay time, inductive load			$t_{d(off)}$		188		ns
Fall time, inductive load			t_f		62		ns
Turn-on energy loss per pulse			E_{on}		3.50		mJ
Turn-off energy loss per pulse			E_{off}		1.68		mJ
Turn-on delay time, inductive load	V_{CC} = 600V, I_C = 40A, R_G = 15Ω, L_σ = 35 nH, V_{GE} = ±15V, T_{vj} = 125℃		$t_{d(on)}$		102		ns
Rise time, inductive load			t_r		100		ns
Turn-off delay time, inductive load			$t_{d(off)}$		211		ns
Fall time, inductive load			t_f		136		ns
Turn-on energy loss per pulse			E_{on}		5.39		mJ
Turn-off energy loss per pulse			E_{off}		2.30		mJ
SC Data	tp≤10us， V_{GE}≤15V， V_{CC}=900V, V_{CEM}≤1200V T_{vj}=125℃		I_{SC}		250		A
Thermal resistance, junction to case	per IGBT		$R_{th(j-c)}$			0.90	K/W
Temperature under switching conditions			$T_{vj\ op}$	-40		150	℃

Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

FRED, Brake-Chopper Absolute Maximum Ratings (@ TC = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	T_{vj} = 25°C	V_{RRM}	1200	V
Continuous DC forward current		I_F	35	A
Repetitive peak forward current	t_P = 1ms	I_{FRM}	70	A
I^2t value for fusing	T_{vj} =150℃, t_P = 10ms, V_R = 0V	I^2t	200	A^2s

FRED, Brake-Chopper Electrical Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage	I_F = 35A, V_{GE} = 0V	T_{vj} = 25°C	V_F		2.00	2.30	V
		T_{vj} = 125°C			1.70		
		T_{vj} = 150°C			1.60		
Peak reverse recovery current	I_F = 35A, V_R = 600V, V_{GE} = -15V, di/dt =300A/μs	T_{vj} = 25°C	I_{RM}		9.5		A
		T_{vj} = 125°C			15.7		
Recovered charge		T_{vj} = 25°C	Q_{rr}		1.36		μC
		T_{vj} = 125°C			3.57		
Peak reverse recovery energy		T_{vj} = 25°C	E_{rec}		0.45		mJ
		T_{vj} = 125°C			1.12		
Thermal resistance, junction to case	per diode		$R_{th(j-c)}$			1.43	K/W
Temperature under switching conditions			$T_{vj\ op}$	-40		150	℃

All product information is copyrighted and subject to legal disclaimers

NTC-Thermistor Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	T_C=25℃	R_{25}		5		KΩ
Deviation of R100	T_C = 100°C, R_{100} = 493 Ω	△R/R	-5		5	%
Power dissipation	T_C = 25°C	P_{25}			20	mW
B-value	$R_2 = R_{25} \exp [B25/50(1/T2 - 1/(298,15 K))]$	$B_{25/50}$		3375		K
B-value	$R_2 = R_{25} \exp [B25/80(1/T2 - 1/(298,15 K))]$	$B_{25/80}$		3411		K
B-value	$R_2 = R_{25} \exp [B25/100(1/T2 - 1/(298,15 K))]$	$B_{25/100}$		3433		K

Module Characteristics

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage (All Terminals Shorted)	RMS, f = 50Hz,1minute	V_{iso}	2.5			KV
Thermal resistance, case to heatsink	per module	$R_{th(c-s)}$		0.009		K/W
Maximum Junction Temperature	Inverter, brake-chopper	$T_{vj\ max}$			175	℃
	rectifier				150	℃
Stray inductance module		L_{SCE}		60		nH
Module lead resistance, terminals - chip	per switch	$R_{CC'+EE'}$		4		mΩ
		$R_{AA'+CC'}$		2		mΩ
Storage Temperature		T_{stg}	-40		125	℃
Mounting torque	Module and heatsink fixed torque M5	M	3.0		6.0	N m

Ordering Information

Device	Marking	Package	Weight	Inner Box	Per Carton
JMG50PM12P3S1	JMG50PM12P3S1	P3	300g/PCS	10PCS	50PCS

Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

Circuit Diagram



Package Outlines (mm)



Unit of measurement: mm

Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

Typical Electrical & Thermal Characteristics

Fig 1. IGBT Output Characteristics
Inverter (typical) VGE=15 V



Fig 2. IGBT Output Characteristics
Inverter (typical)



Fig 3. IGBT Transfer Characteristics
Inverter (typical) VCE=20 V



Fig 4. IGBT Switching Loss vs Ic
Inverter (typical)
Rg=15 Ω, VCE=600 V, VGE=±15 V



Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

Fig 5. IGBT Switching Loss vs. Rg,
Inverter (typical）
Ic=50 A, VCE=600 V, VGE=±15 V



Fig 6. IGBT Transient Thermal Impedance
Inverter



Fig 7. Reverse bias safe operating area
IGBT, Inverter (RBSOA)



Fig 8. FRED Forward Characteristics,
Inverter (typical)



Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

Fig 9. FRED Switching Loss vs. Ic,
Inverter (typical)
Rg=15 Ω, VCE=600 V



Fig 10. FRED Switching Loss vs. Rg,
Inverter (typical)
Ic=50 A, VCE=600 V



Fig 11. FRED Transient Thermal Impedance
Inverter



Fig 12. Diode Rectifier Forward Characteristics



Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

Fig 13. Diode Rectifier Transient Thermal Impedance



Fig 14. IGBT Output Characteristics，
Brake-Chopper (typical) VGE=15 V



Fig 15. FRED Forward Characteristics,
Brake-Chopper (typical)



Fig 16. Temperature characteristics,
NTC thermistor (typical)



Jiangsu JieJie Microelectronics Co., Ltd.
All product information is copyrighted and subject to legal disclaimers

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Semiconductor Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. This information in this document is subject to change without prior notice. Notwithstanding this, Jiangsu JieJie will fully comply with the terms outlined in a signed agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document is the initial release, dated 8 October 2026. This document supersedes and replaces all information previously supplied.

is registered trademark of Jiangsu JieJie Semiconductor Co., Ltd ©2026 Jiangsu JieJie Semiconductor Co., Ltd. All rights reserved.