

**Trench FS IGBT****Features**


- High Power Density
- High mechanical robustness
- Compact design
- Isolated heatsink using DBC technology
- Very low forward voltage drop
- Fast & soft reverse recovery anti-parallel FWD

Product Summary

Parameter	Value	Unit
V_{CES}	1200	V
$I_C(@ T_C = 100^\circ\text{C})$	75	A
$I_{CRM}(@ t_p = 1\text{ms})$	150	A
$V_{CE(sat)}(\text{Typ})$	1.80	V

Applications

- Active Rectifier
- Air Conditioning
- Motor Drives

**IGBT, Inverter Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions	Symbol	Values	Unit
Collector-emitter voltage	$T_{vj} = 25^\circ\text{C}$	V_{CES}	1200	V
Gate-emitter peak voltage		V_{GES}	± 20	V
Continuous collector current	$T_C = 100^\circ\text{C}$	I_C	75	A
Repetitive peak collector current	$t_p = 1\text{ms}$	I_{CRM}	150	A
Total power dissipation	$T_C = 25^\circ\text{C}, T_{vj} = 175^\circ\text{C}$	P_{tot}	380	W

IGBT, Inverter Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	$I_C = 75\text{A}$ $V_{GE} = 15\text{V}$	$T_{vj} = 25^\circ\text{C}$	$V_{CE(sat)}$		1.80	2.15	V
		$T_{vj} = 125^\circ\text{C}$			2.15		
Gate threshold voltage	$V_{CE}=V_{GE}$, $I_C=3\text{mA}$		$V_{GE(th)}$	5.6	6.2	6.8	V
Gate-emitter leakage current	$V_{CE} = 0\text{V}$, $V_{GE} = 20\text{V}$		I_{GES}			400	nA
Collector-emitter cut-off current	$V_{CE}=1200\text{V}$, $V_{GE}=0\text{V}$		I_{CES}			1	mA
Input capacitance	$f = 1\text{MHz}$, $T_{vj} = 25^\circ\text{C}$, $V_{CE} = 25\text{V}$, $V_{GE} = 0\text{V}$		C_{ies}		7.76		nF
Output capacitance			C_{oes}		0.22		nF
Gate charge	$V_{GE} = -15\text{V} \dots +15\text{V}$		Q_G		0.58		μC
Internal gate resistor			R_{Gint}		5.0		Ω ,
Turn-on delay time, inductive load	$V_{CE} = 600\text{V}$, $I_C = 75\text{A}$, $R_G = 15\Omega$, $V_{GE} = \pm 15\text{V}$, $T_{vj} = 25^\circ\text{C}$		$t_{d(on)}$		219		ns
Rise time, inductive load			t_r		134		ns
Turn-off delay time, inductive load			$t_{d(off)}$		347		ns
Fall time, inductive load			t_f		60		ns
Turn-on energy loss per pulse			E_{on}		12.16		mJ
Turn-off energy loss per pulse			E_{off}		3.81		mJ
Turn-on delay time, inductive load	$V_{CE} = 600\text{V}$, $I_C = 75\text{A}$, $R_G = 15\Omega$, $V_{GE} = \pm 15\text{V}$, $T_{vj} = 125^\circ\text{C}$		$t_{d(on)}$		220		μs
Rise time, inductive load			t_r		145		μs
Turn-off delay time, inductive load			$t_{d(off)}$		379		μs
Fall time, inductive load			t_f		108		μs
Turn-on energy loss per pulse			E_{on}		16.54		mJ
Turn-off energy loss per pulse			E_{off}		4.81		mJ
SC Data	$t_p \leq 10\mu\text{s}$, $V_{GE} \leq 15\text{V}$, $V_{CC} = 900\text{V}$, $T_{vj} = 125^\circ\text{C}$		I_{SC}		460		A
Thermal resistance, junction to case	per IGBT		$R_{th(j-c)}$			0.48	K/W
Temperature under switching conditions			$T_{vj op}$	-40		175	$^\circ\text{C}$

**FRED, Inverter Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	$T_{vj} = 25^\circ\text{C}$	V_{RRM}	1200	V
Continuous DC forward current		I_F	75	A
Repetitive peak forward current	$t_P = 1\text{ms}$	I_{FRM}	150	A

FRED, Inverter Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage	$I_F = 75A$, $V_{GE} = 0V$	$T_{vj} = 25^{\circ}C$	V_F		2.10	2.30	V
		$T_{vj} = 125^{\circ}C$			1.80		
Peak reverse recovery current	$I_F=75A$, $V_R=600V$, $V_{GE}=-15V$, $di/dt=400A/\mu s$	$T_{vj} = 25^{\circ}C$	I_{RM}		12.2		A
		$T_{vj} = 125^{\circ}C$			22.1		
Recovery charge		$T_{vj} = 25^{\circ}C$	Q_{rr}		1.93		μC
		$T_{vj} = 125^{\circ}C$			6.02		
Peak reverse recovery energy		$T_{vj} = 25^{\circ}C$	E_{rec}		0.45		mJ
		$T_{vj} = 125^{\circ}C$			1.42		
Thermal resistance, junction to case	per diode		$R_{th(j-c)}$			0.72	K/W
Temperature under switching conditions			$T_{vj\ op}$	-40		150	$^{\circ}C$

**Diode, Rectifier Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	$T_{vj} = 25^\circ\text{C}$	V_{RRM}	1600	V
Bridge output current	$T_C = 80^\circ\text{C}$	$I_{D(AV)}$	75	A
Repetitive peak forward current	$t_P = 10\text{ ms}, T_{vj} = 25^\circ\text{C}$	I_{FSM}	1000	A
	$t_P = 10\text{ ms}, T_{vj} = 150^\circ\text{C}$		800	
I^2t value for fusing	$t_P = 10\text{ ms}, T_{vj} = 25^\circ\text{C}$	I^2t	5000	A^2s
	$t_P = 10\text{ ms}, T_{vj} = 150^\circ\text{C}$		3200	

Diode, Rectifier Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$T_{vj} = 150^\circ\text{C}, I_F = 75\text{A}$	V_F		1.0		V
Reverse current	$T_{vj} = 150^\circ\text{C}, V_R = 1600\text{V}$	I_R		2.0		mA
Thermal resistance, junction to case	per diode	$R_{th(j-c)}$			0.60	K/W
Temperature under switching conditions		$T_{vj\text{ op}}$	-40		150	$^\circ\text{C}$

IGBT, Brake-Chopper Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Collector-emitter voltage	$T_{vj} = 25^\circ\text{C}$	V_{CES}	1200	V
Gate-emitter peak voltage		V_{GES}	± 20	V
Continuous collector current	$T_C = 100^\circ\text{C}$	I_C	50	A
Repetitive peak collector current	$t_P = 1\text{ms}$	I_{CRM}	100	A
Total power dissipation	$T_C = 25^\circ\text{C}, T_{vj} = 175^\circ\text{C}$	P_{tot}	308	W

**IGBT, Brake-Chopper Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	$I_C = 50\text{A}$, $V_{GE} = 15\text{V}$	$T_{vj} = 25^\circ\text{C}$	$V_{CE(sat)}$		1.80	2.15	V
		$T_{vj} = 125^\circ\text{C}$			2.10		
Gate threshold voltage	$V_{CE}=V_{GE}$, $I_C=2.0\text{mA}$,		$V_{GE(th)}$	5.6	6.2	6.8	V
Gate-emitter leakage current	$V_{CE} = 0\text{V}$, $V_{GE} = 20\text{V}$		I_{GES}			400	nA
Collector-emitter cut-off current	$V_{CE}=1200\text{V}$, $V_{GE}=0\text{V}$		I_{CES}			1	mA
Input capacitance	$f = 1\text{MHz}$, $T_{vj} = 25^\circ\text{C}$, $V_{CE} = 25\text{V}$, $V_{GE} = 0\text{V}$		C_{ies}		5.18		nF
Output capacitance			C_{oes}		0.15		nF
Gate charge	$V_{GE} = -15\text{V} \dots +15\text{V}$		Q_G		0.39		μC
Internal gate resistor			R_{Gint}		0		Ω
Turn-on delay time, inductive load	$V_{CC} = 600\text{V}$, $I_C = 50\text{A}$, $R_G = 15\Omega$, $V_{GE} = \pm 15\text{V}$, $T_{vj} = 25^\circ\text{C}$		$t_{d(on)}$		108		ns
Rise time, inductive load			t_r		96		ns
Turn-off delay time, inductive load			$t_{d(off)}$		219		ns
Fall time, inductive load			t_f		137		ns
Turn-on energy loss per pulse			E_{on}		4.20		mJ
Turn-off energy loss per pulse			E_{off}		2.98		mJ
Turn-on delay time, inductive load	$V_{CC} = 600\text{V}$, $I_C = 150\text{A}$, $R_G = 15\Omega$, $V_{GE} = \pm 15\text{V}$, $T_{vj} = 125^\circ\text{C}$		$t_{d(on)}$		108		ns
Rise time, inductive load			t_r		99		ns
Turn-off delay time, inductive load			$t_{d(off)}$		257		ns
Fall time, inductive load			t_f		204		ns
Turn-on energy loss per pulse			E_{on}		6.00		mJ
Turn-off energy loss per pulse			E_{off}		4.06		mJ
SC Data	$t_p \leq 10\mu\text{s}$, $V_{GE} \leq 15\text{V}$, $V_{CC} = 900\text{V}$, $T_{vj} = 125^\circ\text{C}$		I_{SC}		300		A
Thermal resistance, junction to case	per IGBT		$R_{th(j-c)}$			0.60	K/W
Temperature under switching conditions			$T_{vj op}$	-40		150	$^\circ\text{C}$

**FRED, Brake-Chopper Absolute Maximum Ratings (@ TC = 25°C unless otherwise specified)**

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	$T_{vj} = 25^{\circ}\text{C}$	V_{RRM}	1200	V
Continuous DC forward current		I_F	35	A
Repetitive peak forward current	$t_P = 1\text{ms}$	I_{FRM}	70	A

FRED, Brake-Chopper Electrical Characteristics (@ TC = 25°C unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage	$I_F = 35A$, $V_{GE} = 0V$	$T_{vj} = 25^{\circ}C$	V_F		2.00	2.30	V
		$T_{vj} = 125^{\circ}C$			1.70		
Peak reverse recovery current	$I_F = 35A$, $V_R = 600V$, $V_{GE} = -15V$, $di/dt = 400A/\mu s$	$T_{vj} = 25^{\circ}C$	I_{RM}		12.7		A
		$T_{vj} = 125^{\circ}C$			19.5		
Recovered charge		$T_{vj} = 25^{\circ}C$	Q_{rr}		1.81		μC
		$T_{vj} = 125^{\circ}C$			4.51		
Peak reverse recovery energy		$T_{vj} = 25^{\circ}C$	E_{rec}		0.64		mJ
		$T_{vj} = 125^{\circ}C$			1.57		
Thermal resistance, junction to case	per diode		$R_{th(j-c)}$			1.43	K/W
Temperature under switching conditions			$T_{vj\ op}$	-40		175	$^{\circ}C$

**NTC-Thermistor Characteristics (@ T_C = 25°C unless otherwise specified)**

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	T _C =25°C	R ₂₅		5		KΩ
Deviation of R100	T _C = 100°C, R ₁₀₀ = 493 Ω	ΔR/R	-5		5	%
Power dissipation	T _C = 25°C	P ₂₅			20	mW
B-value	$R_2 = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298,15 \text{ K}))]$	B _{25/50}		3375		K
B-value	$R_2 = R_{25} \exp [B_{25/80}(1/T_2 - 1/(298,15 \text{ K}))]$	B _{25/80}		3411		K
B-value	$R_2 = R_{25} \exp [B_{25/100}(1/T_2 - 1/(298,15 \text{ K}))]$	B _{25/100}		3433		K


Module Characteristics

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage (All Terminals Shorted)	RMS, f = 50Hz, 1minute	V _{iso}	2.5			KV
Thermal resistance, case to heatsink	per module	R _{th(c-s)}		0.009		K/W
Maximum Junction Temperature	Inverter, brake-chopper	T _{vj max}			175	°C
	rectifier				150	°C
Stray inductance module		L _{SCE}		25		nH
Module lead resistance, terminals - chip	per switch	R _{CC'+EE'}		1.6		mΩ
		R _{AA'+CC'}		1.1		mΩ
Storage Temperature		T _{stg}	-40		125	°C
Mounting force per clamp		F	3.0		6.0	N


Ordering Information

Device	Marking	Package	Weight	Inner Box	Per Carton
JMG75PM12P3S1	JMG75PM12P3S1	P3	300g/PCS	10PCS	50PCS

Circuit Diagram



Package Outlines (mm)



Typical Electrical & Thermal Characteristics

Fig 1. IGBT Output Characteristics
Inverter (typical) $V_{GE}=15\text{ V}$




Fig 2. IGBT Output Characteristics
Inverter (typical)




Fig 3. IGBT Transfer Characteristics
Inverter (typical) $V_{CE}=20\text{ V}$




Fig 4. IGBT Switching Loss vs I_c
Inverter (typical)
 $R_g=15\ \Omega$, $V_{CE}=600\text{ V}$, $V_{GE}=\pm 15\text{ V}$




Fig 5. IGBT Switching Loss vs. R_g ,
Inverter (typical)
 $I_c=75\text{ A}$, $V_{CE}=600\text{ V}$, $V_{GE}=\pm 15\text{ V}$




Fig 6. Reverse bias safe operating area
IGBT, Inverter (RBSOA)




Fig 7. FRED Forward Characteristics,
Inverter (typical)




Fig 8. FRED Switching Loss vs. I_c ,
Inverter (typical)
 $R_g=15\text{ }\Omega$, $V_{CE}=600\text{ V}$




Fig 9. FRED Switching Loss vs. R_g ,
Inverter (typical)
 $I_c=75\text{ A}$, $V_{CE}=600\text{ V}$




Fig 10. Diode Rectifier Forward Characteristics




Fig 11. IGBT Output Characteristics,
Brake-Chopper (typical) $V_{GE}=15\text{ V}$




Fig 12. FRED Forward Characteristics,
Brake-Chopper (typical)





Fig 13. Temperature characteristics,
NTC thermistor (typical)





Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Semiconductor Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. This information in this document is subject to change without prior notice. Notwithstanding this, Jiangsu JieJie will fully comply with the terms outlined in a signed agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document is the initial release, dated 10 August 2026. This document supersedes and replaces all information previously supplied.

 is registered trademark of Jiangsu JieJie Semiconductor Co., Lt ©2026 Jiangsu JieJie Semiconductor Co., Ltd. All rights reserved.