



## JCT1655SJ 55A SCRs


Rev.2.1

**DESCRIPTION:**

with high ability to withstand the shock loading of large current, JCT1655SJ SCRs provide high dv/dt rate with strong resistance to electromagnetic interference. They are especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc,UPS .Package TO-247J is RoHS compliant. (2011/68/EU)

**MAIN FEATURES**

Symbol	JCT1655SJ	Unit
$V_{DRM}/ V_{RRM}$	1600	V
$I_{T(RMS)}$	55	A
$I_{GT}$	10 ~ 80	mA

**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Value	Unit
Storage junction temperature range	$T_{stg}$	-40~150	°C
Operating junction temperature range	$T_j$	-40~150	°C
Operating temperature range	$T_{op}$	-40~125	°C
Repetitive peak off-state voltage	$V_{DRM}$	1600	V
Repetitive peak reverse voltage	$V_{RRM}$	1600	V
Average on-state current	$I_{T(AV)}$	35	A
RMS on-state current	$I_{T(RMS)}$	55	A
Non repetitive surge peak on-state current (tp=10ms)	$I_{TSM}$	550	A
$I^2t$ value for fusing (tp=10ms)	$I^2t$	1500	$A^2s$
Critical rate of rise of on-state current ( $I_G=2 \times I_{GT}$ )	$dI/dt$	200	$A/\mu s$
Peak gate current	$I_{GM}$	5	A
Peak gate power	$P_{GM}$	10	W
Average gate power dissipation	$P_{G(AV)}$	1	W

Peak pulse voltage (T <sub>j</sub> =25°C; non-repetitive,off-state;FIG.7)	V <sub>pp</sub>	1.1	kV
--	-----------------	-----	----

**ELECTRICAL CHARACTERISTICS (T<sub>j</sub>=25°C unless otherwise specified)**



Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	
I <sub>GT</sub>	V <sub>D</sub> =12V R <sub>L</sub> =30Ω	10	-	80	mA
V <sub>GT</sub>		-	-	1.5	V
V <sub>GD</sub>	V <sub>D</sub> =V <sub>DRM</sub> T <sub>j</sub> =150°C	0.25	-	-	V
I <sub>L</sub>	I <sub>G</sub> =1.2 I <sub>GT</sub>	-	-	250	mA
I <sub>H</sub>	I <sub>T</sub> =1A	-	-	200	mA
dv/dt	V <sub>D</sub> =2/3V <sub>DRM</sub> T <sub>j</sub> =150°C Gate Open	2000	-	-	V/μs
t <sub>on</sub>	I <sub>G</sub> =80mA I <sub>A</sub> =400mA I <sub>R</sub> =40mA T <sub>j</sub> =25°C	-	10	-	μs
t <sub>off</sub>		-	150	-	μs

**STATIC CHARACTERISTICS**

Symbol	Parameter		Value(MAX)	Unit
V <sub>TM</sub>	I <sub>TM</sub> =80A tp=380μs	T <sub>j</sub> =25°C	1.6	V
V <sub>TO</sub>	Threshold voltage	T <sub>j</sub> =150°C	1.12	V
R <sub>d</sub>	Dynamic resistance	T <sub>j</sub> =150°C	6.57	mΩ
I <sub>DRM</sub>	V <sub>D</sub> =V <sub>DRM</sub> V <sub>R</sub> =V <sub>RRM</sub>	T <sub>j</sub> =25°C	10	μA
I <sub>RRM</sub>		T <sub>j</sub> =150°C	8	mA

**THERMAL RESISTANCES**

Symbol	Parameter		Value	Unit
R <sub>th(j-c)</sub>	junction to case(DC)	TO-247J	0.64	°C/W

**ORDERING INFORMATION****MARKING**







**FIG.1** Maximum power dissipation versus RMS on-state current**FIG.3:** Surge peak on-state current versus number of cycles**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10\text{ms}$ , and corresponding value of  $\frac{dI}{dt}$  ( $dI/dt < 200\text{A}/\mu\text{s}$ )**FIG.2:** RMS on-state current versus case temperature**FIG.4:** On-state characteristics (maximum values)**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature

FIG.7: Test circuit for inductive and resistive loads to IEC-61000-4-5 standards




## ORDERING INFORMATION

Order code	Voltage $V_{DRM}/V_{RRM}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
JCT1655SJ	1600	10~80	TO-247J	30	Tube

## Document Revision History


Date	Revision	Changes
Mar 16, 2022	1	Last update
May 26, 2022	2.1	Add Vpp & t <sub>on</sub> & t <sub>off</sub>

## PACKAGE MECHANICAL DATA



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.50	15.80	16.10	0.610	0.622	0.634
B	20.80	21.00	22.20	0.819	0.827	0.835
C	19.70	20.00	20.30	0.776	0.787	0.799
D	1.80	2.00	2.20	0.071	0.079	0.087
E	1.90	2.10	2.30	0.075	0.083	0.091
F	1.00	1.20	1.40	0.039	0.047	0.055
G	5.25		5.65	0.207		0.222
H	4.80	5.00	5.20	0.189	0.197	0.205
J	1.90	2.00	2.10	0.075	0.079	0.083
K	2.20	2.35	2.50	0.087	0.093	0.098
L	0.41	0.60	0.79	0.016	0.024	0.031

## DELIVERY MODE



PACKAGE	OUTLINE	TUBE (PCS)	INNER BOX (PCS)	PER CARTON
TO-247J	TUBE	30	450	2,250



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2022 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.