




## JCTx20 Series 20A SCRs

Rev.6.0

**DESCRIPTION:**

With high ability to withstand the shock loading of large current, JCTx20 SCRs provide high dv/dt rate with strong resistance to electromagnetic interference. They are especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc. Package TO-263 is RoHS compliant. (2011/65/EU)

**MAIN FEATURES**

Symbol	JCT620	JCT820
$V_{DRM}/V_{RRM}$	600V	800V
$I_{T(RMS)}$	20A	
$I_{GT}$		$\leq 25mA$

**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Value	Unit
Storage junction temperature range	$T_{stg}$	-40-150	°C
Operating junction temperature range	$T_j$	-40-150	°C
Repetitive peak off-state voltage( $T_j=25°C$ )	$V_{DRM}$	600/800	V
Repetitive peak reverse voltage( $T_j=25°C$ )	$V_{RRM}$	600/800	V
RMS on-state current <small>(<math>T_c=80°C</math>)</small>	$I_{T(RMS)}$	20	A
Non repetitive surge peak on-state current <small>(tp=10ms)</small>	$I_{TSM}$	250	A
$I^2t$ value for fusing (tp=10ms)	$I^2t$	312.5	$A^2s$
Critical rate of rise of on-state current <small>(<math>I_G=2 \times I_{GT}</math>)</small>	$dI/dt$	50	$A/\mu s$
Peak gate current	$I_{GM}$	4	A
Average gate power dissipation	$P_{G(AV)}$	1	W
Peak gate power	$P_{GM}$	5	W

ELECTRICAL CHARACTERISTICS ( $T_j=25^\circ\text{C}$  unless otherwise specified)

Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	
$I_{GT}$	$V_D=12V$ $R_L=33\Omega$	-	-	25	mA
$V_{GT}$		-	-	1.3	V
$V_{GD}$	$V_D=V_{DRM}$ $T_j=150^\circ\text{C}$ $R_L=3.3K\Omega$	0.2	-	-	V
$I_L$	$I_G=1.2I_{GT}$	-	-	70	mA
$I_H$	$I_T=500mA$	-	-	60	mA
$dV/dt$	$V_D=2/3V_{DRM}$ Gate Open $T_j=150^\circ\text{C}$	200	-	-	V/ $\mu$ s

## STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX)	Unit
$V_{TM}$	$I_{TM}=40A$	$t_p=380\mu\text{s}$	1.55	V
$I_{DRM}$	$V_D=V_{DRM}$	$T_j=25^\circ\text{C}$	5	$\mu$ A
$I_{RRM}$		$T_j=150^\circ\text{C}$	4	mA


## THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	junction to case(AC)	TO-263	2.5	°C/W
$R_{th(j-a)}$	junction to ambient		45	

## ORDERING INFORMATION


J	CT	6	20	E
JieJie Microelectronics Co.,Ltd	SCRs			E:TO-263 ETR:TO-263(Tape&Reel)
		6: $V_{DRM} / V_{RRM} \geq 600V$		
		8: $V_{DRM} / V_{RRM} \geq 800V$		
			IT(RMS):20A	

## PACKAGE MECHANICAL DATA





Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.90		10.20	0.390		0.402
B	14.70		15.80	0.579		0.622
C	9.4		9.6	0.37		0.378
D		2.54			0.100	
E	1.20		1.40	0.047		0.055
F	0.75		0.85	0.029		0.033
G			1.75			0.069
H	4.40		4.70	0.173		0.185
J	2.30		2.70	0.091		0.106
K	0.38		0.55	0.015		0.022
L	0	0.10	0.25	0	0.004	0.010
M	1.25		1.35	0.049		0.053

## FOOTPRINT-TO-263 (dimensions in mm)




## MARKING




## PACKAGE INFORMATION

PACKAGE	OUTLINE	TUBE (PCS)	INNER BOX (PCS)	PER CARTON
TO-263	TUBE	50	1,000	6,000
TO-263	TUBE	50	1,000	8,000
PACKAGE	OUTLINE	REEL (PCS)	PER CARTON (PCS)	TAPE & REEL
TO-263	TAPING	800	4,000	13 inch


**FIG.1:** Maximum power dissipation versus RMS on-state current




**FIG.3:** Surge peak on-state current versus number of cycles




**FIG.2:** RMS on-state current versus ambient temperature (printed circuit board FR4, copper thickness:35μm)(full cycle)




**FIG.4:** On-state characteristics (maximum values)



**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10\text{ms}$ , and corresponding value of  $I^2t$




**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature



## SOLDERING PARAMETERS

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min ( $T_{s(\min)}$ )	+150 °C
	-Temperature Max ( $T_{s(\max)}$ )	+200 °C
	-Time (Min to Max) ( $t_s$ )	60-180 secs.
Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak)	3 °C/sec. Max	
$T_{s(\max)}$ to $T_L$ - Ramp-up Rate	3 °C/sec. Max	
Reflow	-Temperature( $T_L$ ) (Liquidus)	+217 °C
	-Temperature( $t_L$ )	60-150 secs.
Peak Temp ( $T_p$ )	+260(+0/-5) °C	
Time within 5 °C of actual Peak Temp ( $t_p$ )	20-40secs.	
Ramp-down Rate	6 °C/sec. Max	
Time 25 °C to Peak Temp ( $T_p$ )	8 min. Max	
Do not exceed	+260 °C	



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document is the sixth version which is made in 27-Jan.-2019. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2019Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.