


**DESCRIPTION:**

T06xxH series triacs of high junction temperature with high dv/dt rate with strong resistance to electromagnetic interference provide high ability to withstand the shock loading of large current. They are especially recommended for use on inductive load and high environment temperature condition.

Package TO-252 & TO-263 are RoHS compliant. (2011/65/EU)

**MAIN FEATURES**

Symbol	Value	Unit
$I_{T(RMS)}$	6	A
$V_{DRM} / V_{RRM}$	600/800	V
$T_{jmax}$	150	°C

**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Value	Unit
Storage junction temperature range	$T_{stg}$	-40-150	°C
Operating junction temperature range	$T_j$	-40-150	°C
Repetitive peak off-state voltage( $T_j=25^\circ C$ )	$V_{DRM}$	600/800	V
Repetitive peak reverse voltage( $T_j=25^\circ C$ )	$V_{RRM}$	600/800	V
RMS on-state current ( $T_c=100^\circ C$ )	$I_{T(RMS)}$	6	A
TO-252-4R ( $T_c=100^\circ C$ )			
TO-263 ( $T_c=113^\circ C$ )			
Non repetitive surge peak on-state current (full cycle, $F=50Hz$ )	$I_{TSM}$	60	A
$I^2t$ value for fusing ( $t_p=10ms$ )	$I^2t$	21	A <sup>2</sup> s
Critical rate of rise of on-state current ( $I_G=2 \times I_{GT}$ )	$dI/dt$	50	A/μs
Peak gate current	$I_{GM}$	4	A
Average gate power dissipation	$P_{G(AV)}$	1	W
Peak gate power	$P_{GM}$	5	W

**ELECTRICAL CHARACTERISTICS ( $T_j=25^\circ C$  unless otherwise specified)**

Symbol	Test Condition	Quadrant		Value				Unit
				T0610H	T0620H	T0635H	T0650H	
I <sub>GT</sub>	V <sub>D</sub> =12V R <sub>L</sub> =33Ω	I - II - III	MAX	10	20	35	50	mA
V <sub>GT</sub>		I - II - III	MAX	1.3				V
V <sub>GD</sub>	V <sub>D</sub> =V <sub>DRM</sub> T <sub>j</sub> =150°C R <sub>L</sub> =3.3KΩ	I - II - III	MIN	0.2				V
I <sub>L</sub>	I <sub>G</sub> =1.2I <sub>GT</sub>	I - III	MAX	20	40	50	70	mA
		II		35	55	70	100	
I <sub>H</sub>	I <sub>T</sub> =100mA		MAX	20	30	45	60	mA
dV/dt	V <sub>D</sub> =2/3V <sub>DRM</sub> R <sub>GK</sub> =1KΩ T <sub>j</sub> =150°C		MIN	200	500	1000	1500	V/μs

### STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX)	Unit	
V <sub>TM</sub>	I <sub>TM</sub> =8.5A	t <sub>p</sub> =380μs	1.4	V	
I <sub>DRM</sub>		T <sub>j</sub> =25°C	5	μA	
I <sub>RRM</sub>	V <sub>D</sub> =V <sub>DRM</sub>	V <sub>R</sub> =V <sub>RRM</sub>	T <sub>j</sub> =150°C	1	mA


### THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
R <sub>th(j-c)</sub>	junction to case(AC)	TO-252-4R	1.9	°C/W
		TO-263	1.5	
R <sub>th(j-a)</sub>	junction to ambient	TO-252-4R	70	°C/W
		TO-263	45	

## ORDERING INFORMATION


T	06	20	H	-6	K	
Triacs					E:TO-263	
					K:TO-252-4R	
					ETR:TO-263(Tape&Reel)	
					KTR:TO-252-4R(Tape&Reel)	
					6:V <sub>DRM</sub> / V <sub>RRM</sub> ≥ 600V	
					8:V <sub>DRM</sub> / V <sub>RRM</sub> ≥ 800V	
					High junction temperature	

## PACKAGE MECHANICAL DATA




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.90		10.20	0.390		0.402
B	14.70		15.80	0.579		0.622
C	9.4		9.6	0.37		0.378
D		2.54			0.100	
E	1.20		1.40	0.047		0.055
F	0.75		0.85	0.029		0.033
G			1.75			0.069
H	4.40		4.70	0.173		0.185
J	2.30		2.70	0.091		0.106
K	0.38		0.55	0.015		0.022
L	0	0.10	0.25	0	0.004	0.010
M	1.25		1.35	0.049		0.053

## FOOTPRINT-TO-263 (dimensions in mm)




## PACKAGE MECHANICAL DATA





TO-252-4R

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.10		2.50	0.083		0.098
A2	0		0.10	0		0.004
B	0.66		0.86	0.026		0.034
B2	5.18		5.48	0.202		0.216
C	0.40		0.60	0.016		0.024
C2	0.44		0.58	0.017		0.023
D	5.90		6.30	0.232		0.248
D1	5.30REF			0.209REF		
E	6.40		6.80	0.252		0.268
E1	4.63			0.182		
G	4.47		4.67	0.176		0.184
H	9.50		10.70	0.374		0.421
L	1.09		1.21	0.043		0.048
L2	1.35		1.65	0.053		0.065
V1		7°			7°	
V2	0°		6°	0°		6°

## FOOTPRINT-TO-252-4R (dimensions in mm)




**MARKING**

Year	<b>XXX XXX</b>	Production
Month		Code


**PACKAGE INFORMATION**

PACKAGE	OUTLINE	TUBE (PCS)	INNER BOX (PCS)	PER CARTON
TO-263	TUBE	50	1,000	6,000
TO-252-4R	TUBE	80	4,000	32,000
PACKAGE	OUTLINE	REEL (PCS)	PER CARTON (PCS)	TAPE & REEL
TO-263	TAPING	800	4,000	13 inch
TO-252-4R	TAPING	2,500	25,000	13 inch


**FIG.1:** Maximum power dissipation versus RMS on-state current




**FIG.3:** Surge peak on-state current versus number of cycles




**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 20\text{ms}$ , and corresponding value of  $I^2t$  ( $dI/dt < 50\text{A}/\mu\text{s}$ )




**FIG.2:** RMS on-state current versus case temperature



**FIG.4:** On-state characteristics (maximum values)




**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature



## SOLDERING PARAMETERS

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min ( $T_{s(\min)}$ )	+150°C
	-Temperature Max( $T_{s(\max)}$ )	+200°C
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak)		3°C/sec. Max
$T_{s(\max)}$ to $T_L$ - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature( $T_L$ )(Liquidus)	+217°C
	-Temperature( $t_L$ )	60-150 secs.
Peak Temp ( $T_p$ )		+260(+0/-5)°C
Time within 5°C of actual Peak Temp ( $t_p$ )		20-40secs.
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp ( $T_p$ )		8 min. Max
Do not exceed		+260°C



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the ninth version which is made in 11-Apr.-2019. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2019 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.