




BCR20PM-16L 20A TRIACs

Rev.1

DESCRIPTION:

BCR20PM-16L triacs, with high ability to withstand the shock loading of large current, provide high dv/dt rate with strong resistance to electromagnetic interference. With high commutation performances, 3 quadrants products especially recommended for use on inductive load. From all three terminals to external heatsink, BCR20PM-16L provides a rated insulation voltage of 2000 V_{RMS}, complying with UL standards (File ref: E252906). Package TO-220F is RoHS compliant. (2011/65/EU)



MAIN FEATURES

| Symbol | Value | Unit |
|-------------------------------------|-------|------|
| T _j | 150 | °C |
| I _{T(RMS)} | 20 | A |
| V _{DRM} / V _{RRM} | 800 | V |

ABSOLUTE MAXIMUM RATINGS

| Parameter | Symbol | Value | Unit |
|--|---------------------|---------|------------------|
| Storage junction temperature range | T _{stg} | -40-150 | °C |
| Operating junction temperature range | T _j | -40-150 | °C |
| Repetitive peak off-state voltage (T _j =150°C) | V _{DRM} | 700 | V |
| Repetitive peak reverse voltage (T _j =150°C) | V _{DRM} | 700 | V |
| Repetitive peak off-state voltage (T _j =125°C) | V _{DRM} | 800 | V |
| Repetitive peak reverse voltage (T _j =125°C) | V _{DRM} | 800 | V |
| RMS on-state current (T _c =85°C) | I _{T(RMS)} | 20 | A |
| Non repetitive surge peak on-state current (full cycle, F=50Hz) | I _{TSM} | 200 | A |
| I ² t value for fusing (tp=10ms) | I ² t | 200 | A ² s |
| Critical rate of rise of on-state current (I _G =2×I _{GT}) | dI/dt | 100 | A/μs |

| | | | |
|--------------------------------|--------------------|----|---|
| Peak gate current | I _{GM} | 4 | A |
| Average gate power dissipation | P _{G(AV)} | 1 | W |
| Peak gate power | P _{GM} | 10 | W |

ELECTRICAL CHARACTERISTICS (T_j=25°C unless otherwise specified)

| Symbol | Test Condition | Quadrant | | Value | Unit |
|-----------------|---|--------------|-----|-------|------|
| I _{GT} | V _D =12V R _L =33Ω | I - II - III | MAX | 35 | mA |
| V _{GT} | | I - II - III | MAX | 1.3 | V |
| V _{GD} | V _D =V _{DRM} T _j =150°C R _L =3.3KΩ | I - II - III | MIN | 0.2 | V |
| I _L | I _G =1.2I _{GT} | I - III | MAX | 60 | mA |
| | | II | | 70 | |
| I _H | I _T =100mA | | MAX | 50 | mA |
| dV/dt | V _D =2/3V _{DRM} Gate Open T _j =150°C | | MIN | 500 | V/μs |
| (dV/dt)c | (dI/dt)c=8.8A/ms T _j =150°C | | MIN | 7 | V/μs |

STATIC CHARACTERISTICS

| Symbol | Parameter | | Value(MAX) | Unit | |
|------------------|----------------------------------|----------------------------------|-----------------------|------|----|
| V _{TM} | I _{TM} =28A | t _p =380μs | T _j =25°C | 1.55 | V |
| I _{DRM} | | | T _j =25°C | 5 | μA |
| I _{RRM} | V _D =V _{DRM} | V _R =V _{RRM} | T _j =150°C | 2.5 | mA |

THERMAL RESISTANCES

| Symbol | Parameter | | Value | Unit |
|----------------------|----------------------|--------------|-------|------|
| R _{th(j-c)} | junction to case(AC) | TO-220F(Ins) | 2.1 | °C/W |






MARKING**FIG.1:** Maximum power dissipation versus RMS on-state current**FIG.3:** Surge peak on-state current versus number of cycles**FIG.2:** RMS on-state current versus case temperature**FIG.4:** On-state characteristics (maximum values)



FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 20\text{ms}$, and corresponding value of I^2t ($dI/dt < 100\text{A}/\mu\text{s}$)





FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature




ORDERING INFORMATION

| Order code | Voltage V_{DRM}/V_{RRM} (V) | IGT(mA) | Package | Base qty. (pcs) | Delivery mode |
|--------------------|-------------------------------|-----------|---------------------|-----------------|---------------|
| BCR20PM-16L | 800 | 35 | TO-220F(Ins) | 50 | Tube |

Document Revision History


| Date | Revision | Changes |
|--------------|----------|-------------|
| Mar 27, 2022 | 1 | Last update |

PACKAGE MECHANICAL DATA



| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.50 | | 4.90 | 0.177 | | 0.193 |
| B | 0.74 | 0.80 | 0.83 | 0.029 | 0.031 | 0.033 |
| C | 0.47 | | 0.65 | 0.019 | | 0.026 |
| C2 | 2.45 | | 2.75 | 0.096 | | 0.108 |
| C3 | 2.60 | | 3.00 | 0.102 | | 0.118 |
| D | 8.80 | | 9.30 | 0.346 | | 0.366 |
| E | 9.80 | | 10.4 | 0.386 | | 0.410 |
| F | 6.40 | | 6.80 | 0.252 | | 0.268 |
| G | 2.40 | | 2.70 | 0.094 | | 0.106 |
| H | 28.0 | | 29.8 | 1.102 | | 1.173 |
| L1 | | 3.63 | | | 0.143 | |
| L2 | 1.14 | | 1.70 | 0.045 | | 0.067 |
| L3 | | 3.30 | | | 0.130 | |
| V1 | | 45° | | | 45° | |

DELIVERY MODE



| PACKAGE | OUTLINE | TUBE (PCS) | INNER BOX (PCS) | PER CARTON |
|---------|---------|---------------|--------------------|------------|
| TO-220F | TUBE | 50 | 1,000 | 5,000 |



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2022 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.