



JMD150KE16ST

Diode Modules

Features


- Low forward voltage drop
- Fully insulated package
- Easy to use and parallel
- Industry standard outline
- Designed and qualified for industrial level

Product Summary

Parameter	Value	Unit
V_{RRM}	1600	V
$I_{F(AV)}$	150	A
$I_{FSM}(@ t_p = 10ms)$	2500	A
$V_F(Max)$	1.25	V

Applications

- Welding
- SMPS



Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	$T_{vj} = 25^\circ\text{C}$	V_{RRM}	1600	V
Non-repetitive peak reverse voltage	$T_{vj} = 25^\circ\text{C}$	V_{RSM}	1700	V
Average on-state current	$T_C = 50^\circ\text{C}$, per diode	$I_{F(AV)}$	150	A
Forward surge current	1/2 cycle, Sine wave, 50Hz $T_{vj} = 25^\circ\text{C}$	I_{FSM}	2500	A
I^2t Value for fusing		I^2t	88200	A^2s
RMS isolation voltage	A.C 50Hz(1s/1min)	V_{ISO}	3000/2500	V
Junction temperature range		T_J	-40 - 150	$^\circ\text{C}$
Storage temperature range		T_{stg}	-40 - 125	$^\circ\text{C}$

**Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$I_F = 150\text{A}$, $T_{vj} = 25^\circ\text{C}$	V_F		1.10	1.25	V
Reverse leakage current	$V_R = V_{RRM}$, $T_{vj} = 25^\circ\text{C}$	I_R			200	μA
	$V_R = V_{RRM}$, $T_{vj} = 150^\circ\text{C}$				10	mA





Thermal Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Thermal resistance, junction to case	per diode	$R_{th(j-c)}$			0.55	K/W
Thermal resistance, case to heatsink	per module	$R_{th(c-s)}$		0.12		K/W
Mounting torque	Base plate to heatsink screw M4	M	1.0		1.5	N·m
	Electrode to terminal screw M4		1.0		1.3	N·m


Ordering Information


Device	Marking	Package	Weight	Inner Box	Per Carton
JMD150KE16ST	JMD150KE16ST	ST	29g/PCS	80 PCS	160 PCS

Typical Electrical & Thermal Characteristics

FIG.1: Forward characteristics(per diode)

FIG.2: Peak on-state surge current

FIG.3: Forward current vs. case temperature

FIG.4: Maximum transient thermal impedance
 $R_{th(j-c)}$ (°C/W) Junction-to-case(per diode)


Circuit Diagram



Package Outlines (mm)


Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.1	4.2	4.4	0.161	0.165	0.173
B	38.0	38.2	38.4	1.496	1.504	1.512
C	31.1	31.5	31.9	1.224	1.240	1.256
D	30.1	30.2	30.3	1.185	1.189	1.193
E	14.8	15.0	15.2	0.583	0.591	0.598
F	4.1	4.2	4.4	0.161	0.165	0.173
G	12.3	12.5	12.7	0.484	0.492	0.500
H		4.2			0.165	
I		21.6			0.850	
J		2			0.079	
K		4.05			0.159	
L		9.5			0.374	
M	11.6	11.9	12.2	0.457	0.469	0.480
N	24.7	25.1	25.5	0.972	0.988	1.004
O		0.8			0.031	
P		2.6			0.102	
Q		1.7			0.067	
R		8			0.315	
S	4.1	4.2	4.4	0.161	0.165	0.173
T		10.7			0.421	
U		1			0.039	
Y	89°	90°	91°	89°	90°	91°

Technical requirements:

1. Unmarked tolerances of dimension are performed in accordance with GB/T 1804-2000 Level C
2. Unmarked tolerances of form and position are performed in accordance with GB/T 1184-1996 Level L

Unit of measurement: mm



Jiangsu JieJie Semiconductor Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. This information in this document is subject to change without prior notice. Notwithstanding this, Jiangsu JieJie will fully comply with the terms outlined in a signed agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document is the initial release, dated 3 July 2026. This document supersedes and replaces all information previously supplied.

 is registered trademark of Jiangsu JieJie Semiconductor Co., Lt ©2026 Jiangsu JieJie Semiconductor Co., Ltd. All rights reserved.