

**Multifunctional integration Modules****Features**


- Three phase bridge and a thyristor
- Low forward voltage
- High wave surging capability

Product Summary

Parameter	Value	Unit
V_{RRM}	1600	V
I_D	75	A
$I_{FSM}(@ t_p = 10ms)$	900	A
$V_F(Max)$	1.40	V

Applications

- Inverter for AC or DC motor control
- Current stabilized power supply
- Switching power supply

**Thyristor Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage		V_{DRM} $/RRM$	1600	V
Non-repetitive peak reverse voltage	$T_{vj} = 25^\circ\text{C}$	V_{DSM} $/RSM$	1700	V
Bridge output current	$T_C = 85^\circ\text{C}$	$I_{D(AV)}$	75	A
Repetitive peak forward current	$t_P = 10 \text{ ms}$, $T_{vj} = 25^\circ\text{C}$	I_{TSM}	900	A
I^2t value for fusing	$t_P = 10 \text{ ms}$, $T_{vj} = 25^\circ\text{C}$	I^2t	4050	A ² s
Critical rate of rise of on-state current		di/dt	150	A/ μs
Critical rate of rise of voltage	$V_D = 2/3 V_{DRM}$ $T_J = 125^\circ\text{C}$ Gate Open	dv/dt	1000	V/ μs

**Thyristor Rectifier Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$I_T = 75\text{A}$	V_{TM}		1.10	1.30	V
Repetitive peak off-state current	$V_D = V_{DRM}, T_{vj} = 25^\circ\text{C}$	I_{DRM}			0.1	mA
	$V_D = V_{DRM}, T_{vj} = 125^\circ\text{C}$				20	mA
Reverse leakage current	$V_R = V_{RRM}, T_{vj} = 25^\circ\text{C}$	I_{RRM}			0.1	mA
	$V_R = V_{RRM}, T_{vj} = 125^\circ\text{C}$				20	mA
Threshold voltage	For power loss calculation only $T_{vj} = 125^\circ\text{C}$,	V_{TO}			0.85	V
Dynamic resistance	$T_{vj} = 125^\circ\text{C}$,	r_T			2.5	m Ω
Triggering gate voltage	$V_D = 12\text{V}, R_L = 30\Omega$	V_{GT}			1.8	V
Triggering gate current	$V_D = 12\text{V}, R_L = 30\Omega$	I_{GT}	20		120	mA
Holding current	$I_T = 1\text{A}$	I_H			250	mA
Latching current	$I_G = 1.2 I_{GT}$	I_L			300	mA
Non triggering gate voltage	$V_D = V_{DRM}, T_{vj} = 125^\circ\text{C}$	V_{GD}	0.25			V
Thermal resistance, junction to case	per diode	R_{thJC}			0.30	K/W
Temperature under operating conditions		T_{vjOP}	-40		125	$^\circ\text{C}$

Diode Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage		V_{RRM}	1600	V
Non-repetitive peak reverse voltage		V_{RSM}	1700	V
Output current	$T_C = 100^\circ\text{C}$	I_D	75	A
Forward surge current	1/2 cycle, Sine wave, 50Hz $T_{vj} = 25^\circ\text{C}$	I_{FSM}	900	A
I^2t value for fusing		I^2t	4050	A ² s
Temperature under operating conditions		T_{vjOP}	-40 ~ +150	$^\circ\text{C}$

**Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)**

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$I_D = 100\text{A}$, $T_{vj} = 25^\circ\text{C}$	V_F		1.20	1.40	V
Reverse leakage current	$V_R = V_{RRM}$, $T_{vj} = 25^\circ\text{C}$	I_{RRM}			0.1	mA
	$V_R = V_{RRM}$, $T_{vj} = 150^\circ\text{C}$				20	mA
Thermal resistance, junction to case	per diode	R_{thJC}			0.20	K/W


Module Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
RMS isolation voltage	A.C 50Hz, 1min	V_{ISO}	3000			V
Thermal resistance, case to heatsink	per module	R_{thCS}			0.10	K/W
Maximum Junction Temperature	Thyristor	$T_{vj\ max}$			125	$^\circ\text{C}$
	Diode				150	$^\circ\text{C}$
Storage temperature range		T_{stg}	-40		125	$^\circ\text{C}$
Mounting torque	To terminals(M5)	M_t	2.55		3.45	N·m
	To heatsinks(M5)	M_s	2.55		3.45	N·m


Ordering Information

Device	Marking	Package	Weight	Inner Box	Per Carton
JMT75DS16L1	JMT75DS16L1	L1	210g/PCS	12 PCS	60 PCS

Circuit Diagram



Package Outlines (mm)





Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Semiconductor Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. This information in this document is subject to change without prior notice. Notwithstanding this, Jiangsu JieJie will fully comply with the terms outlined in a signed agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document is the initial release, dated 3 September 2026 This document supersedes and replaces all information previously supplied.

 is registered trademark of Jiangsu JieJie Semiconductor Co., Lt ©2026 Jiangsu JieJie Semiconductor Co., Ltd. All rights reserved.